

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>G03F 7/20, 7/18, 7/24</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 98/53370</b> <b>(43) International Publication Date:</b> 26 November 1998 (26.11.98)
<b>(21) International Application Number:</b> PCT/US98/10247 <b>(22) International Filing Date:</b> 19 May 1998 (19.05.98)  <b>(30) Priority Data:</b> 60/047,035 19 May 1997 (19.05.97) US  <b>(71) Applicant:</b> DAY INTERNATIONAL, INC. [US/US]; 130 West Second Street, Dayton, OH 45401 (US).  <b>(72) Inventors:</b> MCLEAN, Michael, E.; 104 Springbrook Farms, Waynesville, NC 28786 (US). WOLTERS, Dennis, R.; 2518 Fairmont, Dayton, OH 45419 (US). BOHNSTADT, Allen; 106 Hickory Lane, Mauldin, SC 29662 (US).  <b>(74) Agents:</b> HAGAN, Timothy, W. et al.; Killworth, Gottman, Hagan & Schaeff, L.L.P., One Dayton Centre, Suite 500, One South Main Street, Dayton, OH 45402-2023 (US).		<b>(81) Designated States:</b> AU, BR, CA, CN, JP, MX, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  <b>Published</b> <i>With international search report.</i>
<b>(54) Title:</b> PRINTING PLATE AND METHOD OF MAKING USING DIGITAL IMAGING PHOTOPOLYMERIZATION  <b>(57) Abstract</b>  A printing plate is provided including a support assembly and a relief imaged surface formed directly on the surface of the support assembly by digital photopolymerization. The support assembly may be in the form of a cylindrical sleeve or a flat polymeric base. The printing plate is formed by providing a liquid photopolymer on the surface of the support assembly and irradiating the polymer with a source of actinic to form the relief image. The printing plate is reimagable and may be used in flexographic printing processes as well as other printing applications.		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## PRINTING PLATE AND METHOD OF MAKING USING DIGITAL IMAGING PHOTOPOLYMERIZATION

### BACKGROUND OF THE INVENTION

The present invention relates to a printing plate and method of making it, and  
5 more particularly to such a printing plate having a relief image formed on its surface  
by digital imaging photopolymerization.

Flexography or flexographic printing are terms which have been applied  
broadly to a specialized form of relief printing which utilizes rubber or other  
elastomeric relief plates. Because the inks used for flexography dry very quickly,  
10 flexographic printing has been widely used to print a variety of nonabsorbent surfaces  
including plastics and foils as well as thick substrates such as paperboard. More  
recent improvements in the quality of the rubbery relief plates used in flexographic  
printing has broadened the types of jobs which are printed using this technique.

The rubbery relief plates used in flexography have been made in the past by  
15 casting or pressing a rubber sheet against a metal negative relief surface and then  
hardening the rubber. More recently, the plates have been manufactured using  
photohardenable polymeric compositions. Typically, a sheet of the photohardenable  
composition is covered with a flexible polymeric film and imagewise exposing the  
composition through the film using actinic radiation. The polymeric film and  
20 unhardened portions of the composition are then stripped away and removed, leaving  
the imaged relief surface.

However, problems have remained with flexographic printing plates including  
loss of sharpness in the relief surface caused by the diffraction of the actinic radiation  
passing through the film layer or mask to the surface of the photohardenable  
25 composition and distortion of the rubbery relief surfaces when the plate is mounted  
onto a plate cylinder for printing. Additionally, as the plates are customized for  
individual repetitive printing jobs, the printer must maintain a large inventory of the  
plates typically mounted on a replaceable sleeve, which takes up valuable plant  
space and increases parts costs to the printer.

-2-

Accordingly, needs remain in this art for a printing plate which can be accurately imaged and readily replaced to provide improved print quality while lowering costs to the printer.

### SUMMARY OF THE INVENTION

5       The present invention addresses these needs by providing a printing plate having a relief imaged surface which is reimagable, i.e., the relief image(s) can be removed and new images replaced on the surface. The plate may be utilized in flexographic printing processes. Further, with suitable modifications, the plate may also be useful in other direct and indirect relief printing processes including offset  
10 lithography as well as in intaglio processes such as direct and indirect gravure printing processes. The printing plate of the present invention may be provided as either a cylindrical or flat printing plate.

      In accordance with one aspect of the invention, a printing plate is provided which comprises a support assembly and a relief-imaged surface on the support  
15 assembly. The support assembly may be a composite of one or more layers of metal, fabric, and/or polymer to provide requisite properties of compressibility and conformability as well as a stable support surface for the raised image. The support assembly may take a variety of forms. In one embodiment, the support assembly comprises an expandable, cylindrical sleeve including a base layer, at least one  
20 compressible layer, and a surface layer which includes a relief image. The sleeve is replaceable and can be mounted and demounted onto a metal cylinder or roller using pressurized air. The support assembly is constructed to provide an inner diameter and shape which is mountable onto a cylinder or roller without slippage during the printing process. Alternatively, the support assembly may comprise a flat polymeric  
25 base layer including the relief imaged surface, which base layer can be used in either a flat configuration, or mounted onto a cylinder for printing.

      The relief imaged surface is formed using digital imaging photopolymerization techniques in which a liquid photopolymer layer is provided on the support assembly and is exposed to a light source which emits radiation for a time sufficient to cure and  
30 harden the photopolymer in areas exposed to the radiation. The term

-3-

"photopolymerization" is meant to include both polymer formation and polymer crosslinking and also includes photohardenable compositions. Preferably, a raised relief image of approximately 0.40 to about 1.0 mm is provided. The liquid photopolymer may be any light-sensitive polymer which will cure and harden after exposure to actinic radiation. The photopolymer is preferably selected from the group consisting of acrylates, epoxies, urethanes, and unsaturated polyesters.

In one embodiment of the invention, the relief imaged surface is formed at a digital imaging station using stereolithography techniques. At the imaging station, the support assembly, in the form of a cylindrical sleeve, is immersed into a bath of a liquid photopolymer or meterly coated with liquid polymer in a non-immersive manner. The support assembly is rotated so that successive portions of the support assembly which are covered by the photopolymer are exposed to a source of actinic radiation such as a laser which is translated along or across the surface of the support assembly. Alternatively, the laser may be fixed, and the support assembly translated and rotated appropriately. Those portions of the photopolymer which are exposed to the laser cure and form raised image areas. Laser scanning is repeated until the entire surface is imaged.

The resulting printing plate may then be mounted onto a press and used to print in a conventional manner. Once the particular printing job for which the image was produced has been completed, the imaged sleeve may be demounted and stored for later reuse. Alternatively, the relief image surface may be removed at a reprocessing station, and the surface of the plate prepared for receiving a new image at the digital imaging station. The relief image is preferably removed by an abrading mechanism which mechanically grinds, scrapes, or otherwise cuts away the imaged areas until the surface of the support layer is exposed. Alternatively, the image may be removed by chemically dissolving and washing away the raised image.

Because in a preferred embodiment of the invention, the plate is in the form of a replaceable sleeve, the printer need not tie up a printing cylinder for each plate; the sleeves may be readily demounted and stored. Further, as the image on the printing plate is replaceable, the printer need not maintain a large inventory of plates. This reduces costs. Lastly, as the image is formed digitally from a computer-stored file,

there is no degradation in quality of the image as with masks or film layers so that the image which is printed is sharp and well defined.

Accordingly, it is a feature of the present invention to provide a printing plate and process of manufacture having a digitally formed relief imaged surface which may be utilized in flexographic as well as other printing processes. It is a further feature of the invention to provide a reusable printing plate. These, and other features and advantages of the present invention, will become apparent from the following detailed description, the accompanying drawings, and the appended claims.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a schematic, perspective view of the composite support assembly prior to imaging;

Fig. 2 is a schematic, perspective view of the printing sleeve after imaging;

Fig. 3 is a schematic diagram of a preferred imaging process for the printing sleeve at a digital imaging station; and

Fig. 4 is a schematic diagram of the removal of the image portion of the printing sleeve at a sleeve reprocessing station.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

While the printing plate of the present invention will be described with reference to its preferred use as a printing plate for use in a flexographic printing process, it will be apparent to those skilled in the art that the plate may be modified for use in other direct and indirect printing processes including intaglio and direct and indirect gravure processes. Further, while the printing plate will be described as being in the form of a sleeve mounted onto a cylindrical support assembly, it will be apparent that such a sleeve is capable of taking other forms including a flat plate.

Fig. 1 illustrates one embodiment of the invention in which a schematic of a composite sleeve 10 is shown. The sleeve 10 acts as a support assembly and includes one or more polymer layers including one or more compressible elastomeric layers such as, for example, an inner base polymer layer 12, a compressible layer 14, and a surface layer 16 which provides a stable working surface for the later-applied

-5-

image-bearing layer. Sleeve 10 is designed to be mounted onto (and demounted from) a cylindrically-shaped roller (not shown) through the use of pressurized air which will cause the sleeve to expand slightly to provide clearance during the mounting and demounting. Once the air pressure is removed, the sleeve 10 will  
5 contract tightly about the cylinder and will not slip or slide during printing.

Fig. 2 shows schematically the printing sleeve 10 after an image ("PART B") has been applied to surface 18. The image may take the form of any indicia including numbers, letters, graphics, etc. needed to perform the print job. Generally, for flexographic applications, the image on surface 18 will have a height of approximately  
10 0.40 to about 1.0 mm.

The image is formed on sleeve 10 at a digital imaging station 20 as shown schematically in Fig. 3. There, sleeve 10 is immersed into a bath of a liquid, photopolymer 22 contained in tank 24. Suitable photopolymers are known and are commercially available from a number of companies. Any suitable photocurable or  
15 photohardenable resin may be used in the practice of this invention.

As shown, sleeve 10 may be mounted onto a mandrel 26, the long axis of which is rotated by a suitable drive mechanism such as, for example, a stepper motor 28. The level of liquid photopolymer in the bath is such that the upper surface of the sleeve is substantially level with the upper surface of the polymer bath. Actinic  
20 radiation to activate and harden the polymer is provided from a source 30 which is preferably a laser light source. However, it will be appreciated that other sources of actinic radiation may be utilized within the scope of the present invention.

Laser 30 is mounted so that it can be translated to irradiate parallel to the long axis of sleeve 10. The beam is modulated under the control of a computer 25 to  
25 create a single line of the image to be formed. Computer aided design and drafting software is commercially available from a number of companies and may be used to convert a desired image to be printed into the necessary modulation of the laser beam. After each line of the image is scanned onto the surface of sleeve 10, stepper motor 28 rotates sleeve 10 to position it to receive the next line of information. In this  
30 manner, a relief image is built up on surface 18 of the sleeve. Once imaging has been completed, sleeve 10 is removed from the bath, and any excess, unreacted

-6-

photopolymer is washed away. For extended use, the finished plate may be baked to increase its durability.

Upon finishing image sleeve 10 as is conventional in flexographic applications, the sleeve may then be mounted onto a plate cylinder of a flexographic printing press.

5 Because the image is digitally formed directly onto the cylindrical surface of the sleeve 10, there is no distortion of the image, which remains sharp and well defined. Once a printing job has been completed, sleeve 10 may be demounted and stored for later use (if the print job is repetitive).

Alternatively, the image on surface 18 may be removed at reprocessing station 10 38 and sleeve 10 reused as shown in Fig. 4. There, sleeve 10 is mounted onto another mandrel 32 and rotated about its long axis by a suitable drive mechanism 34. The imaged surface 18 is removed by a suitable polymer abrading mechanism 36 which mechanically grinds, scrapes, or cuts away the image until surface layer 16 on sleeve 10 is exposed. Alternatively, the image may be removed by chemically 15 dissolving and washing away the raised image.

The reprocessed sleeve may then be taken back to digital imaging station 20 where a new image is built up as previously described.

Because the images for each printing job may be stored in computer memory, the printer need not stock in inventory multiple printing sleeves or plates. Rather, 20 each printing job may be created and the same sleeve imaged over and over again. This permits the printer to stock only a minimum number of sleeves, reducing both storage and materials costs. Furthermore, because each print job is digitally imaged directly on the printing sleeve, the print quality is high.

While certain representative embodiments and details have been shown for 25 purposes of illustrating the invention, it will be apparent to those skilled in the art that various changes in the methods and apparatus disclosed herein may be made without departing from the scope of the invention.



-7-

## CLAIMS

1. A printing plate comprising a support assembly and a relief imaged surface on said support assembly, wherein said relief imaged surface has been formed directly onto said support assembly by digital imaging photopolymerization.
- 5 2. A printing plate as claimed in claim 1 in which said support assembly comprises an expandable sleeve including a base layer, at least one compressible layer, and a surface layer including said relief imaged surface.
3. A printing plate as claimed in claim 1 in which said support assembly comprises a polymeric base layer.
- 10 4. A printing plate as claimed in claim 1 in which said relief image is raised from about 0.4 to 1.0 mm.
5. A printing plate as claimed in claim 1 in which said printing plate is reimagable upon removal of said imaged surface.
6. A method of making a printing plate comprising the steps of:  
15 providing a support assembly;  
providing a liquid photopolymer on at least a portion of the surface of said support assembly; and  
irradiating said polymer with a light source for a time sufficient to cure said polymer and form a relief image directly on said support assembly.
- 20 7. A method as claimed in claim 6 in which said photopolymer is prepared from the group consisting of acrylates, epoxies, urethanes, unsaturated polyesters, and mixtures thereof.

-8-

8. The method of claim 6 in which said support assembly comprises an expandable sleeve including a base layer, at least one compressible layer, and a surface layer.
9. A method as claimed in claim 8 in which said support assembly is immersed  
5 into a bath of said liquid photopolymer.
10. A method as claimed in claim 8 in which said support assembly is meterly coated with said liquid photopolymer.
11. The method of claim 6 in which said support assembly comprises a polymeric base layer.
- 10 12. A method as claimed in claim 6 in which said light source comprises a laser.
13. A method as claimed in claim 12 in which said laser is translated over said surface of said support assembly to photopolymerize selected portions of said photopolymer.
14. A method as claimed in claim 6 further including the step of removing said  
15 relief image from the surface of said support assembly.
15. A digital imaging photopolymerization system for providing a printing plate including a support assembly adapted to receive a liquid photopolymer, a source of actinic radiation for irradiating said photopolymer to form a relief image on said support assembly, and a computer for controlling the operation of said system.
- 20 16. The digital imaging system of claim 15 in which said source comprises a laser.

17. A method of making a reimagable printing plate comprising the steps of:  
providing a support assembly;  
providing a relief image on the surface of said support assembly by digital  
imaging photopolymerization to form a printing plate;  
5 mounting said printing plate on a printing device and printing a substrate using  
said relief image;  
demounting said printing plate from said printing device and removing said  
relief image from said printing plate such that said printing plate is adapted to receive  
a new relief imaged surface.
- 10 18. The method as claimed in claim 17 in which said relief image is removed by an  
abrading mechanism.
19. The method as claimed in claim 17 in which said relief image is removed by  
chemically dissolving said relief image.

1/3




FIG. 1





FIG. 2

**2/3**



**SUBSTITUTE SHEET (RULE 26)**

3/3




FIG. 4

# INTERNATIONAL SEARCH REPORT

national Application No

PCT/US 98/10247

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 G03F7/20 G03F7/18 G03F7/24

According to International Patent Classification(IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G03F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 491 368 A (DONNELLY R R & SONS) 24 June 1992	1,4,6,7, 9,10,15, 16
Y	see the whole document	2,3,5,8, 11-14, 17-19
Y	US 4 116 715 A (SMIGGEN FRANK J ET AL) 26 September 1978  see the whole document	2,3,5,8, 11-14, 17-19
Y	DE 42 32 187 A (DU PONT DEUTSCHLAND) 31 March 1994  see the whole document	2,3,5,8, 11-14, 17-19
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

26 August 1998

Date of mailing of the international search report

10/09/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Haenisch, U

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/10247

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 91 13511 A (BACHER GMBH B) 5 September 1991 see the whole document -----	15, 16
X	ANONYMOUS: "Laser Direct Imaging System for Print Band Manufacturing" IBM TECHNICAL DISCLOSURE BULLETIN, vol. 27, no. 10B, March 1985, page 5970 XP002075588 see the whole document -----	15, 16



**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

International Application No

PCT/US 98/10247

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0491368 A	24-06-1992	US 5278027 A CA 2056680 A JP 4316052 A	11-01-1994 19-06-1992 06-11-1992
US 4116715 A	26-09-1978	NONE	
DE 4232187 A	31-03-1994	NONE	
WO 9113511 A	05-09-1991	DE 4007716 A	29-08-1991

**THIS PAGE BLANK (USPTO)**